

Model	XP-350B	XP-350BM
Printing		
Printing method	Direct thermal	
Resolution	203DPI	
Print width	16-82mm	
Printing speed	152mm/s	
Memory	DRAM: 4M, FLASH: 4M	
Print head temperature sensor	Thermal sensitive resistance	
Paper exists detection	Photosensor	
Interface	USB	Serial+USB+LAN
Character size	Font A:1.5×3.0mm(12×24 dots) Font B:1.1×2.1mm(9×17 dots)	
Barcode Character		
Barcode	CODE128, EAN128, ITF, CODE39, CODE93, EAN13, EAN13+2, EAN13+5, EAN8, EAN8+2, EAN8+5, CODABAR, POSTNET, UPC-A, UPCA+2, UPCA+5, UPC-E, UPCE+2, UPC-E+5, CPOST, MSI, MSIC, PLESSEY, ITF14, EAN14	
Internal font	FONT 0 to FONT 8	
Enlargement & rotation	(0°, 90°, 270°, 360°) 1 to 10 times enlargement in both direction; 0°, 90°, 270°, 360° rotation	
Image	Monochromatic PCX, BMP image files can be load to FLASH, DRAM	
Media type		
Paper type	Paper roll, sticker, adhesive sticker, etc	
Paper width	16mm~82mm	
Roll external diameter	MAX 100mm	
Roll inner diameter	MIN 25mm	
Paper off type	Tear off or peel off	
Power		
Power supply input	24VDC, 2.5A	
Physical characteristics		
Weight	1.52KG	
Dimensions	220(D) x 150(W) x 157(H)mm	
Environmental Requirements		
Work environment	5~45 C 20-80%RH(no condensation)	
Storage environment	-40~55 C 93%RH(40,)	